

3158

PRODUCT NAME: PRP – X600 Resin (Dry)

MSDS Document # 4414-01

Rev C Page 1

HAMILTON COMPANY
4970 Energy Way
Reno, Nevada 89502


MATERIAL SAFETY DATA SHEET

Date Prepared: March 13, 2009

Total Number of Pages: 3

RECEIVED

3/13/09

Phone Number (7:00am-3:00pm, Pacific Time): 800-648-5950 or 775-858-3000
Emergency Phone (24 hours): CHEMTREC: 1-800-424-9300; Outside U.S. 1-202-483-7616

Abbreviations: n/a, not available or applicable; n/d, not or none determined

SECTION 1 – MATERIAL IDENTIFICATION AND INFORMATION

Components	CAS #	wt%	OSHA PEL-TWA	ACGIH TLV-TWA	STEL(OSHA@ ACGIG)	ODOR
Poly(dimethylamino propyl-Methacrylamide)	Not assigned	100	n/d	n/d	n/d	n/d

This MSDS is for a range of products, all of which contain dry PRP-X600 resin that is dry. These products can be packaged in any volume (cc) or weight (g), and can contain resin having average particle size from 5 to 20µm. Refer to the product label for actual resin volume and particle size.

CAS# - Chemical Abstract Service Number

OSHA: Occupational Safety and Health Administration

PEL – Permissible Exposure Limit

ACGIH – American Conference of Governmental Industrial Hygienist

TWA – Time-Weighted (8 hour) Average (value to which workers can be exposed for a normal 8 hour day, 40-hr week without ill effects)

TLV – Threshold Limit Value

STEL – Short-term (15 minutes) Exposure Limit

SECTION 2 – PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance: Light brown cake

Odor: None

Melting Point: n/d for polymer

Vapor Pressure: n/a

Boiling Point: n/d for polymer

Vapor Density: Not volatile

Specific Gravity: 1.1 for polymer

Evaporation Rate: n/a

Solubility in water: Polymer is insoluble

Water reactivity: none

The polymer is not volatile.

Product is hydrophobic; to prepare an aqueous slurry, add water slowly while mixing.

Product is made of small diameter particles, up to 20µm (refer to product label for actual particle size).

SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

Material is combustible when exposed to heat or flame, especially if particulates are airborne.

Flash Point: n/d

Auto-Ignition Temperature: n/d

Flammability Limits in Air: n/d

Extinguisher Media: Foam, CO², dry chemical

Special Fire Fighting Procedures: Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires.

Unusual Fire and Explosion Hazards: none

PERMANENT FILE
DO NOT REMOVE

SECTION 4 – REACTIVITY HAZARD DATA

Material is stable. Hazardous polymerization will not occur.

Conditions to avoid: n/d

Materials to avoid: Concentrated nitric acid or other strong oxidizing agents

Hazardous Decomposition Products: n/d

SECTION 5 – HEALTH HAZARD DATA

Primary exposure routes: Ingestion, inhalation, eye and skin contact.

Carcinogen Status: Not listed

Health Hazards: If 5-10 μ m particles are inhaled, they may reach the alveolar region of the lungs and deposit there. To the best of our knowledge, the health effects of this product has not been thoroughly studied.

Signs and Symptoms of Overexposure: Skin or eye irritation; coughing or throat irritation if inhaled.

Medical Conditions Generally Aggravated by Exposure: Chronic respiratory or skin conditions

EMERGENCY FIRST AID PROCEDURES – Seek medical attention for further treatment or observation if necessary

Eye Contact: Flush with copious amounts of water for 15 minutes

Skin Contact: Wash thoroughly with soap and water

Inhalation: Remove to fresh air.

Ingestion: Induce vomiting. Consult a physician.

SECTION 6 – CONTROL AND PROTECTIVE MEASURES

Respiratory Protection: Normal ventilation

Protective Gloves: Thin latex gloves may be used to eliminate skin exposure.

Eye Protection: Wear safety glasses

Other Protective Clothing and Equipment: A dust mask may be worn to prevent inhalation of airborne particles.

Hygienic Work Practices: Keep away from food.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

Handling Information and Recommendations: The dry material is susceptible to static charging and to dispersment in the air. To avoid these conditions and for easier handling, keep the material wet with acetone, water or other liquid.

Steps to be taken if Material is Spilled or Released: Avoid dispersing the dry resin particles into the air. If material is spilled on the floor, it can be slippery. Clean up with soap and water, rinse area with water.

Waste Disposal: According to local, state and federal regulations.

Storage Recommendation: Keep container closed and in a cool place. The product can be made safer by storing the polymer in a liquid that is less flammable and less toxic than acetone. If the resin is stored in slurry form, use a microbial-growth inhibitor such as methanol, acetonitrile, acetone, or dilute sodium azide solution.

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This document will be revised as more information becomes available. If you have questions contact Hamilton Company.