


Data Sheet POLILYTE PLUS XP

The maintenance free POLILYTE PLUS XP sensor is especially designed for processes with high, constant pressure and moderate temperature. The EVEREF-L reference cartridge ensures a long lifetime. The two SINGLE PORES guarantee best measurement results because of direct contact between the sample and the solid POLISOLVE PLUS electrolyte.

Application Fields:

Water, waste water, chemical industry

Specifications:

Serial Number:	Yes
Certificate:	Yes, with measured values in buffer pH 4.01 and pH 7.00
Measuring Method:	Combination electrode, potential measured against reference electrode
Range:	pH 0 ... 14
Zero-Point:	0 ± 20 mV
Sensitivity:	57 ... 59 mV / pH at 25°C
Temperature Range:	0 ... 60°C
Pressure Range:	0 ... 50 bar
Electrolyte:	POLISOLVE PLUS
Reference System:	HAMILTON EVEREF-L
Liquid Earth:	No
Shaft Material:	Glass
Membrane glass:	HAMILTON type H glass
Sample: min Conductivity:	2 µS/cm
Diaphragm:	SINGLE PORE
Number of diaphragm:	2
Steam sterilizable:	No
Autoclavable:	No
CIP:	No
Electrical Connector:	Type S8 – standard pH connector head, suitable for most brand name quality pH cables
Temperature Sensor:	No
ATEX approval:	Yes, CE 0035  1/2 G Ex ia IIC T4/T5/T6
Recommended Storage:	HAMILTON Storage Solution (p/n 238931) or 3M KCl (p/n 238036 or 238936)



Ordering Information:

Part Number	Description	a-length (a)
238 811	Polilyte Plus XP 120	120 mm

Dimensional drawing:

