PRP-X500 7 μ m 4.6 \times 150 mm, PEEK

Specification Sheet (Part/REF # 79573)



Both fast separations and good sample capacity are achievable with PRP-X500 columns.

Product Specifications

| Troduce Specifications | |
|--------------------------------|--|
| Separation Mode | Anion Exchange |
| Stationary Phase | PRP-X500 |
| Format | HPLC Column |
| Hardware Inner Diameter | 4.6 mm |
| Hardware Length | 150 mm |
| Particle Size | 7 μm |
| USP Classification | USP L23 |
| Packing Material Type | Poly(methacryl amido-propyl trimethyl ammonium chloride) |
| Pore Size | Superficially Porous |
| Particle Surface Area (m2/cm3) | 1.4 |
| Pore Volume (cm3/g) | 0.0063 |
| Hardware Material | PEEK |
| Max Pressure | 5,000 psi |
| Exchange Capacity | 1.6 meq/gm |
| Exchange Capacity/Column | 1.92 meq/column |
| Mobile Phase Limits | pH 1-13. 0-100% aqueous, organic modifier |
| Buffer Strength | 0.0-2.0N |
| Temp Limits | 5-30°C |
| Compound Classification | Large Proteins/Labeled DNA |
| иом | 1 EACH |
| | |

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/hplc-columns/79573