

Polyplast PRO RX

Specification Sheet (Part/REF # 238409)



The Polyplast Pro has a robust plastic shaft and notched tip to prevent breakage in applications such as water treatment, fish and algae farming.

Product Specifications

Sensor Family	Polyplast Pro
Sensor Output	Traditional: mV
a-length	120 mm
Electrical Connector	S8
Measurement Principle	Combination electrode; ORP potential measured against reference
Measuring Range	-2000 mV to +2000 mV
pH Glass Resistance	Moderate
ORP Element	Pt wire
Membrane Shape	Spherical
Diaphragm	Single Pore
Number of Diaphragms	1
Electrolyte	Polisolve
Reference System	Ag/AgCl
Liquid Earth	No
Temperature Sensor	No
Diameter	12 mm
Process Connection	PG13,5
Wetted Parts	Platinum Glass EPDM (Ethylene propylene elastomer) SAN (Polystyrene-Acrylonitrile)
O-ring Material	FDA 21 CFR 177.2600; EG 1935/2004; USP <87>; USP <88> Class VI (121 °C)
Serial Number	Yes
Recommended Storage	Hamilton Storage Solution or 3 M KCl
Certificate	No
ATEX Approval	II 1/2 G Ex ia IIB T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
IECEX Approval	II 1/2 G Ex ia IIB T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
Autoclavable	No
CIP	No
Steam Sterilizable	No
Operating Temperature Range	-10 to 40 °C (60 °C short exposure)

Sample min Conductivity	50 µS/cm
Pressure Range bar g	0 to 6 bar