

# EasyFerm Bio HB VP 120 Pt100

Specification Sheet (Part/REF # 243632-2111)



Traditional sensors offer a standard mV output signal and a wide variety of electrical connectors to work with most transmitters and controllers.

## Product Specifications

<b>Sensor Family</b>	EasyFerm Bio
<b>Parameter</b>	pH
<b>Sensor Output</b>	Traditional: mV
<b>a-length</b>	120 mm
<b>Electrical Connector</b>	VP6
<b>Measurement Principle</b>	Combination electrode; pH potential measured against reference
<b>Measuring Range</b>	pH 0 to 14
<b>Sensitivity</b>	57 to 59 mV / pH at 25 °C
<b>Zero Point</b>	0 ± 20 mV
<b>pH Glass</b>	Hamilton type HB glass
<b>pH Glass Resistance</b>	Moderate
<b>Membrane Shape</b>	Spherical
<b>Diaphragm</b>	HP-Coatramic
<b>Number of Diaphragms</b>	1
<b>Electrolyte</b>	Pressurized Foodlyte
<b>Reference System</b>	Hamilton Everef-F, Silver ion barrier included
<b>Liquid Earth</b>	No
<b>Temperature Sensor</b>	Pt100
<b>Diameter</b>	12 mm
<b>Process Connection</b>	PG13,5
<b>Wetted Parts</b>	Glass Ceramic VMQ (Silicone elastomer)
<b>O-ring Material</b>	FDA 21 CFR 177.2600; EG 1935/2004; USP <87>; USP <88> Class VI (121 °C)
<b>Serial Number</b>	Yes
<b>Recommended Storage</b>	Hamilton Storage Solution or 3 M KCl
<b>Certificate</b>	Yes, with measured values in Buffer pH 4.01 and pH 7.00
<b>ATEX Approval</b>	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
<b>IECEX Approval</b>	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
<b>Autoclavable</b>	Yes
<b>CIP</b>	Yes

Steam Sterilizable	Yes
Operating Temperature Range	0 to 140 °C
Sample min Conductivity	100 µS/cm
Pressure Range bar g	0 to 6 bar

Specifications are subject to change without notice

<https://www.hamiltoncompany.com/sensors/243632-2111>

Spec. Version B