

500 µL, Model 1750 Spark Holland SYR, 1/4-28 Threads

Specification Sheet (Part/REF # 54660-01)



The world-famous Hamilton syringe is now available for your Spark Holland Autosampler! Featuring a rugged polytetrafluoroethylene (PTFE) plunger tip for highly reproducible results from injection-to-injection and Hamilton glass barrel surface finish for superior syringe life. These syringes fit the Midas, Triathlon, Endurance and Alias model autosamplers.

Product Specifications

Needle Sold Separately	Yes
Volume	500 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	ChemSeal (C, 1/4"-28)
Needle	No Needle Available
Plunger Style	Side Post Mounting (XL)
Fluid Path	Borosilicate glass, PTFE, PFA
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	80°C / 176°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.128 inches (3.26 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Specifications are subject to change without notice
<https://www.hamiltoncompany.com/syringes/54660-01>

Spec. Version B