

500 µL Microliter Syringe Model 750 N, Cemented Needle, 22 gauge, 2 in, point style 2

Specification Sheet (Part/REF # 80800)



Split/splitless injection consists of a heated chamber with a glass liner into which the sample is injected through the septum. A microsyringe is used to inject the sample through a rubber septum into a flash vaporizer chamber at the head of the column.

Product Specifications

Volume	500 µL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22 gauge
Point Style	2: Curved, Beveled
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.135 inches (3.26 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Needle Inner Diameter	0.0161 inches (0.41 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std Needle Dead Volume	6.81 µL
Sales Quantity	1 syringe per pack

Specifications are subject to change without notice

<https://www.hamiltoncompany.com/syringes/80800>

Spec. Version B