## 100 μL, Model 1710 LT Syringe, Needles Sold Separately

Specification Sheet (Part/REF # 81001)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1  $\mu$ L up to 500  $\mu$ L. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

| •  |  |
|--|--|
| Volume   | 100 μL   |
| Syringe Type   | Gastight   |
| Syringe Series   | 1700   |
| Termination  | Luer Tip (LT)  |
| Needle   | Kel-F Hub  |
| Gauge  | No Needle Included   |
| Point Style  | No Needle Included   |
| Needle Length  | No Needle Included   |
| Fluid Path   | Borosilicate glass, PTFE   |
| Autoclavable   | Yes to 115 °C  |
|  | 100 to 110   |
| Gas Sterilizable   | Yes  |
|  |  |
| Gas Sterilizable   | Yes  |
| Gas Sterilizable Pressure  | Yes<br>1000 psig (68.9 bar)  |
| Gas Sterilizable Pressure Maximum Temperature  | Yes 1000 psig (68.9 bar) 80°C / 176°F  |
| Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature   | Yes  1000 psig (68.9 bar)  80°C / 176°F  10°C / 50°F   |
| Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature  Barrel Inner Diameter                        | Yes  1000 psig (68.9 bar)  80°C / 176°F  10°C / 50°F  0.057 inches (1.46 mm)                         |
| Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature  Barrel Inner Diameter  Barrel Outer Diameter | Yes  1000 psig (68.9 bar)  80°C / 176°F  10°C / 50°F  0.057 inches (1.46 mm)  0.305 inches (7.75 mm) |

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/syringes/81001