2.5 mL, Model 1002 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 2

Specification Sheet (Part/REF # 81417)



The 1000 series syringes are a mid-volume Gastight syringe. This series of syringes is ideal for dispensing volumes from 1 mL up to 100 mL. A variety of different terminations and needle options are available in this series.

Product Specifications

•	
Volume	2.5 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	Luer Tip Cemented Needle (LTN)
Needle	Cemented Needle
Gauge	22 gauge
Point Style	2: Curved, Beveled
Needle Length	2 inch (51 mm)
Fluid Path	SST, Borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Gas Sterilizable Pressure	Yes 200 psig (13.8 bar)
Pressure	200 psig (13.8 bar)
Pressure Maximum Temperature	200 psig (13.8 bar) 50°C / 122°F
Pressure Maximum Temperature Minimum Temperature	200 psig (13.8 bar) 50°C / 122°F 10°C / 50°F
Pressure Maximum Temperature Minimum Temperature Barrel Inner Diameter	200 psig (13.8 bar) 50°C / 122°F 10°C / 50°F 0.287 inches (7.29 mm)
Pressure Maximum Temperature Minimum Temperature Barrel Inner Diameter Barrel Outer Diameter	200 psig (13.8 bar) 50°C / 122°F 10°C / 50°F 0.287 inches (7.29 mm) 0.407 inches (10.3 mm)
Pressure Maximum Temperature Minimum Temperature Barrel Inner Diameter Barrel Outer Diameter Needle Inner Diameter	200 psig (13.8 bar) 50°C / 122°F 10°C / 50°F 0.287 inches (7.29 mm) 0.407 inches (10.3 mm) 0.0161 inches (0.41 mm)
Pressure Maximum Temperature Minimum Temperature Barrel Inner Diameter Barrel Outer Diameter Needle Inner Diameter Needle Outer Diameter	200 psig (13.8 bar) 50°C / 122°F 10°C / 50°F 0.287 inches (7.29 mm) 0.407 inches (10.3 mm) 0.0161 inches (0.41 mm) 0.0283 inches (0.72 mm)

Specifications are subject to change without notice

https://www.hamiltoncompany.com/syringes/81417

Spec. Version B