250 μ L, Model 1725 Syringe, Large Removable Needle, 22s gauge, 2 in, point style 2

Specification Sheet (Part/REF # 81130)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1 μ L up to 500 μ L. A variety of different terminations and needle options are available in this series.

Product Specifications

| Volume | 250 μL |
|------------------------|-------------------------------|
| Syringe Type | Gastight |
| Syringe Series | 1700 |
| Termination | Removable Needle (RN) |
| Needle | Large RN |
| Gauge | 22s gauge |
| Point Style | 2: Curved, Beveled |
| Needle Length | 2 inch (51 mm) |
| Fluid Path | SST, Borosilicate glass, PTFE |
| Autoclavable | Yes |
| Gas Sterilizable | Yes |
| Pressure | 500 psig (34.5 bar) |
| Maximum Temperature | 80°C / 176°F |
| Minimum Temperature | 10°C / 50°F |
| Barrel Inner Diameter | 0.091 inches (2.30 mm) |
| Barrel Outer Diameter | 0.305 inches (7.75 mm) |
| Needle Inner Diameter | 0.0059 inches (0.15 mm) |
| Needle Outer Diameter | 0.0283 inches (0.72 mm) |
| Std Needle Dead Volume | 1.13 μL |
| Sales Quantity | 1 syringe per pack |
| | Contraction D |

Specifications are subject to change without notice

Spec. Version B

https://www.hamiltoncompany.com/syringes/81130