10 mL, Model 1010 TLL SYR, Instrument Syringe

Specification Sheet (Part/REF # 9880-50)



Designing a system that needs a syringe? Utilize our syringe experts to get the best connections and materials of construction for your application.

Product Specifications

| - | |
|------------------------|-------------------------------|
| Volume | 10 mL |
| Syringe Type | Gastight |
| Syringe Series | 1000 |
| Termination | PTFE Luer Lock (TLL) |
| Needle | Instrument Syringe |
| Gauge | No Needle Included |
| Point Style | No Needle Included |
| Needle Length | No Needle Included |
| Plunger Style | Side Post Mounting (XL) |
| Fluid Path | Borosilicate glass, PTFE, PFA |
| Autoclavable | No |
| Gas Sterilizable | Yes |
| Pressure | 200 psig (13.8 bar) |
| Maximum Temperature | 80°C/176°F |
| Minimum Temperature | 10°C / 50°F |
| Barrel Inner Diameter | 0.574 inches (14.6 mm) |
| Barrel Outer Diameter | 0.695 inches (17.7 mm) |
| Std Needle Dead Volume | N/A |
| Sales Quantity | 1 syringe per pack |
| | |

Specifications are subject to change without notice https://www.hamiltoncompany.com/syringes/9880-50 Spec. Version B