50 μ L, Model 705 LT SYR, Needles Sold Separately

Specification Sheet (Part/REF # 80501)



The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from 0.5 μ L up to 500 μ L. A variety of different terminations and needle options are available in this series.

Product Specifications

•	
Volume	50 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Luer Tip (LT)
Needle	Kel-F Hub
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	SST, borosilicate glass
Autoclavable	Yes to 115 °C
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	80°C / 176°F
Maximum Temperature Minimum Temperature	
	80°C / 176°F
Minimum Temperature	80°C / 176°F 10°C / 50°F
Minimum Temperature Barrel Inner Diameter	80°C / 176°F 10°C / 50°F 0.041 inches (1.03 mm)
Minimum Temperature Barrel Inner Diameter Barrel Outer Diameter	80°C / 176°F 10°C / 50°F 0.041 inches (1.03 mm) 0.305 inches (7.75 mm)

Specifications are subject to change without notice

https://www.hamiltoncompany.com/syringes/80501

Spec. Version B