## 3-5 Hamaflon, HV, MVP Valve

Specification Sheet (Part/REF # 99900-01)



Shop all MVP/4 Valves

## **Product Specifications**

| •                       |                                |
|-------------------------|--------------------------------|
| Valve Model             | 3-5                            |
| Valve Model Description | Distribution Flow Path 3-ports |
| Fluid Path              | CTFE/Hamaflon                  |
| Valve Size              | HV                             |
| Nominal Port Diameter   | 0.059 inch (1.5 mm)            |
| Housing Material        | CTFE                           |
| Actuated                | MVP/4                          |
| Break Away Torque       | 25 oz-in (176 mNm)             |
| Panel Mounting          | No                             |
| Panel Thickness         | N/A                            |
| Thread Depth            | 0.250 (6.35 mm)                |
| Threaded Connection     | 1/4-28                         |
| Operating Temp High     | 40 °C (104 °F)                 |
| Operating Temp Low      | 15 °C (59 °F)                  |
| Operating Pressure      | 0 to 100 psig (0 to 6.9 bar)   |
| Storage Temp High       | 65 °C (149 °F)                 |
| Storage Temp Low        | -29 °C (-20 °F)                |
|                         |                                |

Specifications are subject to change without notice https://www.hamiltoncompany.com/valves/99900-01 Spec. Version B